

**Annex 1****WAV technical Specification**

(All dimensions minimum and maximum for model range approved)

Wheelchair Access Entrance Dimensions

	Variant / Version	
	All	
Width (mm)	755	
Height (mm)	1295	

Designated Travelling Position (add table / extend table as necessary)

	Variant / Version	
	Fwd wheelchair position	Rwd wheelchair position
Width (mm) (min and max)	760	760
Length (mm) (min and max)	1165	987 Seat in, 1250 Seat out
Wheelchair space gradient (°)	0.2	0.2
Maximum seated eyeline height (mm)	1250	1243
Internal roof height (mm)	1407	1359
Maximum wheelchair mass (kg)	150	150

Maximum access dimensions (add table / extend table as necessary)**Wheel chair position 1**

	Variant / Version	
	All	
Width (mm)	Forward Position: 760	
Length (mm)	Forward Position: 1165	
Height (mm)	Forward Position: 1407	

Ramp (if fitted)

	Variant / Version	
	All	
Width (mm)	747	
Length (mm)	1125	
Angle when deployed onto road (°)	12.4	
For side entry WAV, angle when deployed onto 125mm pavement (°)	N/A	
Position	Side / Rear ⁽¹⁾	Side / Rear ⁽⁴⁾
Safe working load (kg)	300	
Attachment method	Permanent / Removable ⁽⁴⁾	Permanent / Removable ⁽⁴⁾
Maximum ramp projection when deployed (mm)	850	